



relationships **FORGED**
solutions **CAST**

U.V. International LLC

360 Mt. Kemble Ave. Suite#2000, Morristown, NJ 07960



P: (877) 993-9454 | F: (973) 775-1680

uvnj@uvintl.com | www.uvintl.com

Ductile Iron Threaded Mechanical Joint Adapter Bell

ANSI /AWWA C110/A21.10

DMA1214



UV Item Number	Nom Pipe Size	Flange Outer Diameter	Bolt Circle	B.Hole UNC tapped	No of Holes	Flange Thickness	Overall Thickness	Diameter of Hub	Thread Length	Weight lbs
DMA0003	3	7.69	6.19	5/8 - 11	4	0.94	4.12	4.50	0.94	11
DMA0004	4	9.12	7.50	3/4 - 10	4	1.00	4.25	5.32	1.00	13
DMA0006	6	11.12	9.50	3/4 - 10	6	1.06	4.43	7.56	1.15	20
DMA0008	8	13.37	11.75	3/4 - 10	6	1.12	4.75	9.73	1.38	28
DMA0010	10	15.69	14.00	3/4 - 10	8	1.19	4.87	12.06	1.50	41
DMA0012	12	17.94	16.25	3/4 - 10	8	1.25	5.12	14.16	1.75	53
DMA0014	14	20.31	18.75	3/4 - 10	10	1.31	6.50	16.25	1.87	78
DMA0016	16	22.56	21.00	3/4 - 10	12	1.38	6.75	18.44	2.06	97
DMA0018	18	24.83	23.25	3/4 - 10	12	1.44	7.00	20.53	2.25	120
DMA0020	20	27.08	25.50	3/4 - 10	14	1.50	7.25	22.63	2.43	146
DMA0024	24	31.58	30.00	3/4 - 10	16	1.62	7.50	26.82	2.75	175
DMA0030	30	39.12	36.88	1 - 8	20	1.81	9.13	32.75	3.38	283
DMA0036	36	46.00	43.75	1 - 8	24	2.00	9.75	39.12	4.00	482
DMA0042	42	53.12	50.62	1 1/4 - 7	28	2.00	10.50	46.00	4.00	642
DMA0048	48	60.00	57.50	1 1/4 - 7	32	2.00	11.00	52.25	4.12	811

* Dimensions are in inches

- ▶ Material: Ductile Iron ASTM A536 Grade 65-45-12
- ▶ MJ Bell in accordance with ANSI/AWWA C110/A21.10
- ▶ Flange Machined, Drilled and Faced
- ▶ Threaded in accordance with ANSI/ASME B1.20.1(National Pipe Taper Threads)
- ▶ Bolt Holes are UNC threaded for stud bolts
- ▶ Coating : Bare

To Order Call: (973) 775 1660 X 4; Fax: (973) 775 1680

uvnj@uvintl.com www.uvintl.com